

UPGRADABLE ATM

HT2845-SR9500VSU

Transform ATM to high performance Cash Recycling Machine with India's First Upgradable ATM

Be future ready. Upgrade as per your needs.

Timely investment in Self Service Channel



Upgrade ATM to CRM as per convenience: Basis catchment requirements, upgrade the ATM to CRM conveniently.

Timely investment: Avoid risk of being conservative. Invest at appropriate time to get timely revenue.

Transform ATM to CRM in just 4 hours



Lower TAT for providing CRM services: Flexibility with banks to upgrade ATM to CRM with minimal downtime.

Quick upgrade: Upgrade time is just 4 hours as against ~20 days to replace ATM with CRM.

Safeguard your investment



Avoidance of sunk cost or unproductive costs: No extra cost towards ATM replacement, site modification, etc. Also save time and energy as there is no need to search for an alternative site for the idle ATM.

Be future ready



Forward-looking approach: Be future ready for evolving market requirements and new payments methods (eg. Interoperable Cash deposits, UPI based deposits).

By choosing Upgradable ATM, banks can seamlessly convert ATM to CRM (Cash Recycling Machine) and prepare their site for deposit transactions, getting the best of both worlds.



Features:

Compact Design

Minimum maintenance area is 996mm x 1340mm.

The installation area is small and can be installed in a variety of locations, which makes it easier for you to provide services to your customers.



Intuitive Design

A multi-touch panel suitable for Web-UI enables intuitive operation, so your services can be smoothly delivered to customers on PC/smartphone as well as on this machine.



Simple Design

Aiming for high uptime by optimizing/simplifying the configuration of the cash transfer route and each unit, so you can reliably provide services to your customers. Improving speed and efficiency, especially by integrating controls and route optimization of Cash module.



General

Dimensions : 490mm(W)×780mm(D)×1,446mm(H)

Weight : 410kg(Including Options)

Type : Front Loading

Cabinet Security : UL 291 24H level 1 safe

Cash Module

No. of notes per trn : Up to 200 notes

Cassette (CRM) : 4+1 [4 recycling cassettes + 1 acceptance cassette]

Cassette (ATM) : 4+1 [4 cassettes + 1 purge bin]

Handling Speed : Up to 8 notes/sec

Customer Interface

15-inch multi-touch screen

8 function keys (Optional)

PCI compliant stainless steel encryption PIN pad

EMV certified motorized/dip card reader

Thermal receipt printer

Fingerprint reader (Optional)

Contactless card reader (Optional)

1D/2D Barcode reader (Optional)

Audio jack

Power Supply

Input : AC100~240V ± 10%,50/60Hz

Power Consumption : In-operation Approx.400W,Stand-by Approx.120W

Built-in UPS(option)

Security

- Anti-skimming card slot
- Screen privacy filter
- Customer awareness mirror
- Note tracing function
- PIN pad privacy shield
- Face / cash slot cameras (Optional)

For enquiry please email to info@hitachi-payments.com

Hitachi Payment Services

Corporate Office

Hitachi Payment Services Pvt. Ltd.: # 401, 4th Floor, Silver Metropolis,
Jai Coach Compound, Off Western Express Highway, Goregaon (East), Mumbai - 400 063.

Tel: +91 22 3954 1800, +91 22 4878 1000

www.hitachi-payments.com



Scan here to visit the website